

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1 – 4 (cancelled)

5. (previously presented) A corona wire damper for damping at least one corona wire mounted to a charger body, comprising:

a damping pad; and,

a pad holder holding said damping pad and attachable to the charger body such that said damping pad contacts the at least one corona wire;

wherein said pad holder comprises a pair of arms configured to wrap-around engage mating portions of the charger body, and each arm comprises a protuberance.

6 – 9 (cancelled)

10. (previously presented) A corona charger for an electrographic printer, comprising:

a charger body;

at least one corona wire mounted to said charger body;

a damping pad; and,

a pad holder holding said damping pad and attached to said charger body such that said damping pad contacts said at least one corona wire;

wherein said pad holder comprises a pair of arms wrapping around mating portions of said charger body, and each arm comprises a protuberance that engages a mating structure on said charger body.

11-13 (cancelled)

14. (previously presented) A method for damping at least one corona wire mounted to a charger body in an electrographic printer, comprising:  
contacting said at least one corona wire with a damping pad;  
further comprising rotating said damping pad to contact a fresh surface of said pad with said at least one corona wire.

15. (previously presented) A method for damping at least one corona wire mounted to a charger body in an electrographic printer, comprising:  
contacting said at least one corona wire with a damping pad;  
further comprising moving said damping pad laterally relative to said at least one corona wire to contact a fresh surface of said pad with said at least one corona wire.

16. (previously presented) A method for damping at least one corona wire mounted to a charger body in an electrographic printer, comprising:  
contacting said at least one corona wire with a damping pad;  
further comprising holding said damping pad in a pad holder having a pair of arms, and registering said pad holder to said charger body with a protuberance formed in each arm.

17-19 (cancelled)